

V.11 DECK HARDWARE PORTLIGHTS & HATCHES

ROUGERS






You might think it started in 1976. I would rather say the late 40s or early 50s.

A few nautical miles west of Marstrand there's a small island with a light house called *Pater Noster*. It was built in 1868. Pater Noster is the latin name of the prayer *Our Father* and its origin is much older than the light house itself. In the old days when seamen and fishermen approached Marstrand, they said that prayer in hope of reaching their destination.

Marstrand is a fabulous sailing venue but it can quickly turn dangerous with hard winds, rough seas, a strong current and thousands of treacherous rocks.

This is where I grew up in the 40s and 50s, this is where I learned to both love and fear the sea, this



In 1976 I invented the revolutionary *Super Ring* and founded Rutgerson Marin. I wanted to offer modern, user-friendly and reliable boat fittings to sailors all over the world. Today, after 40 years, these values are still true and we will continue to develop smart and innovative solutions for many years to come.

At Rutgerson we don't compromise about quality. Never have. Never will. You just don't do that if you're born and raised in a place like Marstrand.

Göran Rutgerson FOUNDER AND OWNER



CONTENTS

PORTLIGHTS	4
Oval Portlights	6
Elliptical Portlights	8
Rectangular Portlights	10
Curved-rectangular Portlights	
Round Portlights	13
Customised Portlights	
Inner Frames	15
Aluminum Templates	16
Acrylic Glass	16
Mosquito Net	
Spare Parts	17

HATCHES 1	18
Classic Hatches	
Master Flush Hatches	21
Escape Hatches	22
Accessories	23

BLOCKS	
RAW Blocks	27
RAW Cheek Block	32
RAW Toggle-head Blocks	33
RAW Blocks with Snap Shackles	
ROC Blocks	34
ROC Block Becket	35
ROC Block Ball Joint Stand-up	35
Spring Stand-ups	36
Mainsheet Tackles & Lines	36
Chafe Covers	37
Wire Blocks	37
Deck Blocks	37
ROC Deck Blocks	
Foot Blocks	39

SNATCH BLOCK 40	
LOW FRICTION RINGS 41	
STAINLESS STEEL FITTINGS42Padeyes42Snap Shackles42Pelican Hooks42	
ROPE CLUTCHES 43 RC75 43 RC120 44 RC2000 45 Accessories 45	
DECK ORGANISERS	
DECK FILLERS	
TRACK SYSTEMS 50 Mainsheet Systems 50 Cappa Systems 57	

Mainsheet Systems	50
Genoa Systems	57
Self-tacking Jib Systems	60



Photo: Curtesy ©CBreschi

PORTLIGHTS

Rutgerson portlights are famous for their seamless design as well as extensive range of shapes and sizes. Portlights let light and air into the boat and keep water and moisture out. They also make a strong visual statement about the quality of the craft.

The Rutgerson portlights are deep drawn in Swedish stainless steel 316L and polished to a high lustre. The seamless construction ensures that the strength and elegant design will last far longer than conventional alternatives.

The tinted acrylic glass is either 10 or 15mm thick and the window area of Rutgerson portlights is in general largest on the market. An essential factor is the seal around the opening window and frame. The most common materials used by other brands are cellular rubber or compressible foam, but they tend to disintegrate gradually over the years. These materials are also vulnerable to distortion due to the high pressure on the seal when the portlight is closed. Rutgerson portlights are equipped with a high quality silicone rubber gasket, which is very durable and thus prevents leakage.

The locking mechanism consists of Delrin spiral knobs, designed so that the closing pressure can be varied.

We offer a wide range of inner frames including frames made of stainless steel, which is completely unique. Inner frames are always included and the alternatives are chromed ABS (CH), Off-White ABS (OW) or Stainless Steel (RF).

The portlights are available in oval, elliptical, rectangular, curved-rectangular and round shapes in both fixed and opening models. All portlights are available in several different depths. They have a simple, fast installation and each product comes with a cut-out template on the packaging. A range of optional mosquito nets is also available.

All portlights may be used in Area I, IIb, III & IV as specified in EN ISO 12216 on Recreational Craft of Any Design Category on Any Boat Type according to Council Directive 2013/53/EU Area 1





The hinges are made of polyamide and have a friction function, which enables the glass to stay open in different positions.



The seal is made of silicon rubber, which is the most durable solution and gives the portlight maximum performance. Additionally, the seal is incorporated into the acrylic glass.



The acetal knobs are designed so that the closing pressure can be varied.



Portlight shapes



Oval Portlight

403x204 mm

Elliptical Portlight

450x195 mm 485x225 mm



Rectangular Portlight

370x164 mm 402x195 mm 428x179 mm 700x191 mm

Curved-rectangular Portlight

405x140 mm 440x180 mm

Round Portlight

250 mm





Oval Portlights







Stainless steel reinforcement

Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]
Oval Portlight 40	3 x 204 mm Opening	acrylic with e	xclusive stainless	reinforced glass	frame			
A1120-200RF	SS reinforcement	Opening	Stainless Steel	Stainless steel	8 - 14	14	1910	10
A1120-200CH	SS reinforcement	Opening	Stainless Steel	Chrome	8 - 33	14	1990	10
A1120-2000W	SS reinforcement	Opening	Stainless Steel	Off white	8 - 33	14	1990	10
A1130-200RF	SS reinforcement	Opening	Stainless Steel	Stainless steel	15 - 27	27	2050	10
A1130-200CH	SS reinforcement	Opening	Stainless Steel	Chrome	27 - 46	27	2130	10
A1130-2000W	SS reinforcement	Opening	Stainless Steel	Off white	27 - 46	27	2130	10
A1150-200RF	SS reinforcement	Opening	Stainless Steel	Stainless steel	28 - 47	47	2150	10
A1150-200CH	SS reinforcement	Opening	Stainless Steel	Chrome	47 - 66	47	2060	10
A1150-2000W	SS reinforcement	Opening	Stainless Steel	Off white	47 - 66	47	2060	10
Oval Portlight 40	3 x 204 mm Opening	acrylic		^				·
A1320-200RF	Regular	Opening	Stainless Steel	Stainless steel	8 - 14	14	1640	15
A1320-200CH	Regular	Opening	Stainless Steel	Chrome	8 - 33	14	1710	15
A1320-2000W	Regular	Opening	Stainless Steel	Off white	8 - 33	14	1710	15
A1330-200RF	Regular	Opening	Stainless Steel	Stainless steel	15 - 27	27	1780	15
A1330-200CH	Regular	Opening	Stainless Steel	Chrome	27 - 46	27	1860	15
A1330-2000W	Regular	Opening	Stainless Steel	Off white	27 - 46	27	1860	15
A1350-200RF	Regular	Opening	Stainless Steel	Stainless steel	28 - 47	47	1990	15
A1350-200CH	Regular	Opening	Stainless Steel	Chrome	47 - 66	47	2060	15
A1350-2000W	Regular	Opening	Stainless Steel	Off white	47 - 66	47	2060	15
Oval Portlight 40	3 x 204 mm Fixed ac	rylic						
A1125-200RF	Regular	Fixed	Stainless Steel	Stainless steel	8 - 14	14	1340	10
A1125-2000W	Regular	Fixed	Stainless Steel	Off white	8 - 33	14	1500	10
A1135-200RF	Regular	Fixed	Stainless Steel	Stainless steel	15 - 27	27	1450	10
A1135-2000W	Regular	Fixed	Stainless Steel	Off white	27 - 46	27	1600	10
A1155-200RF	Regular	Fixed	Stainless Steel	Stainless steel	28 -47	47	1660	10
A1155-2000W	Regular	Fixed	Stainless Steel	Off white	47 -66	47	1800	10
Oval Engine Roo	m Ventilation 403 x 2	04 mm		Air inlet area				
A1495-200				26 000 mm3	8 - 70		1670	



Engine room ventilation



Stainless steel reinforcement means that there is a frame on the inside of the acrylic glass that increases the rigidity of the portlight. It also gives the portlight a high-class impression when viewed from the inside.



Oval Cutout






Photo: Curtesy of Nimbus Boats Sweden AB - Nimbus 405 Coupe

Elliptical Portlights







Fixed

Stainless steel reinforcement

Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]
Elliptical Portlight	450 x 195 mm Ooer	ing acrylic wit	h exclusive stainle	ess reinforced gla	ss frame			
A3120-190RF	SS reinforcement	Opening	Stainless Steel	Stainless steel	8 - 15	15	1850	10
A3120-190CH	SS reinforcement	Opening	Stainless Steel	Chrome	8 - 32	15	1750	10
A3120-1900W	SS reinforcement	Opening	Stainless Steel	Off white	8 - 32	15	1750	10
A3130-190RF	SS reinforcement	Opening	Stainless Steel	Stainless steel	16 - 27	27	2060	10
A3130-190CH	SS reinforcement	Opening	Stainless Steel	Chrome	27 - 44	27	1950	10
A3130-1900W	SS reinforcement	Opening	Stainless Steel	Off white	27 - 44	27	1950	10
Elliptical Portlight	450 x 195 mm Oper	ning acrylic						
A3320-190RF	Regular	Opening	Stainless Steel	Stainless steel	8 - 15	15	1600	15
A3320-190CH	Regular	Opening	Stainless Steel	Chrome	8 - 32	15	1500	15
A3320-1900W	Regular	Opening	Stainless Steel	Off white	8 - 32	15	1500	15
A3330-190RF	Regular	Opening	Stainless Steel	Stainless steel	16 - 27	27	1800	15
A3330-190CH	Regular	Opening	Stainless Steel	Chrome	27 - 44	27	1700	15
A3330-1900W	Regular	Opening	Stainless Steel	Off white	27 - 44	27	1700	15
Elliptical Portlight	450 x 195 mm Fixed	acrylic						
A3125-190RF	Regular	Fixed	Stainless Steel	Stainless steel	8 - 15	15	1350	10
A3125-190OW	Regular	Fixed	Stainless Steel	Off white	8 - 32	15	1500	10
A3135-190RF	Regular	Fixed	Stainless Steel	Stainless steel	16 - 27	27	1470	10
A3135-190OW	Regular	Fixed	Stainless Steel	Off white	27 - 44	27	1750	10
Elliptical Engine F	Room Ventilation 450	x 195 mm		Air inlet area				
A3495-190				21 000 mm3	8 - 70		1670	



Engine room ventilation



Photo: Curtesy of Viknes Boats









Stainless steel reinforcment

A3395-220

Opening Fixed Rec. hull Depth Weight **Glass Thickness** Part no Туре Function Outer frame Inner frame thickness [mm] [mm] [g] [mm] Elliptical Portlight 485 x 225 mm Opening acrylic with exclusive stainless reinforced glass frame A3130-220RF SS reinforcement Opening Stainless steel Stainless steel 8 - 27 27 2250 10 A3130-220CH 8 - 54 27 10 SS reinforcement Opening Stainless steel Chrome 2250 A3130-2200W Off white 8 - 54 27 2250 10 SS reinforcement Opening Stainless steel 28 - 47 47 10 A3150-220RF SS reinforcement Stainless steel Stainless steel 2500 Opening A3150-220CH 47 - 67 47 2290 10 SS reinforcement Opening Stainless steel Chrome A3150-2200W SS reinforcement Off white 47 - 67 47 2290 10 Opening Stainless steel Elliptical Portlight 485 x 225 mm Opening acrylic A3330-220RF Stainless steel Stainless steel 8 - 27 27 1950 15 Regular Opening A3330-220CH 8 - 54 27 1950 15 Chrome Regular Stainless steel Opening Stainless steel Off white 8 - 54 27 1950 A3330-2200W 15 Regular Opening A3350-220RF Opening Stainless steel Stainless steel 28 - 47 47 2050 15 Regular A3350-220CH Regular Opening Stainless steel Chrome 47 - 67 47 2050 15 A3350-2200W Off white 47 - 67 47 2050 15 Regular Opening Stainless steel Elliptical Portlight 485 x 225 mm Fixed acrylic A3135-220RF Regular Fixed Stainless steel 8 - 15 27 1700 10 Stainless steel A3155-220RF Regular Fixed Stainless steel Stainless steel 28 - 47 47 1850 10 Elliptical Engine Room Ventilation 485 x 225 mm Air inlet area




27 500 mm3

8 - 70

Engine room ventilation

Elliptical Cutout



Outer dimensions	Cut-out dimensions [mm]							
X x Y [mm]	А	В	C Radius	D Radius				
Elliptical Portlight Dimension Guide								
450 x 195	428	173	389	51				
485 x 225	467	205	390	48				

2100

Rectangular Portlights



Opening Black



Opening Stainless steel



Fixed Stainless steel

Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]		
Rectangular Portlight 402 x 195 mm Opening acrylic with exclusive stainless reinforced GLASS FRAME										
A2120-200CH	SS reinforcement	Opening	Stainless steel	Chrome	8 - 43	14	1810	10		
A2120-2000W	SS reinforcement	Opening	Stainless steel	Off white	8 - 43	14	1810	10		
A2130-200CH	SS reinforcement	Opening	Stainless steel	Chrome	26 - 55	26	2040	10		
A2130-2000W	SS reinforcement	Opening	Stainless steel	Off white	26 - 55	26	2040	10		
Rectangular Portlig	ght 402 x 195 mm Op	ening acrylic								
A2320-200B-S	Regular	Opening	Black	Black	8 - 43	14	1600	15		
A2320-200CH	Regular	Opening	Stainless steel	Chrome	8 - 43	14	1600	15		
A2320-2000W	Regular	Opening	Stainless steel	Off white	8 - 43	14	1600	15		
A2320-2000W-S	Regular	Opening	Black	Off white	8 - 43	14	1600	15		
A2330-200CH	Regular	Opening	Stainless steel	Chrome	26 - 55	26	1740	15		
A2330-2000W	Regular	Opening	Stainless steel	Off white	26 - 55	26	1740	15		
Rectangular Portlig	ght 402 x 195 mm Fix	ed acrylic				-				
A2125-200CH	Regular	Fixed	Stainless steel	Chrome	8 - 43	14	1940	10		
A2125-2000W	Regular	Fixed	Stainless steel	Off white	8 - 43	14	1940	10		
A2135-200CH	Regular	Fixed	Stainless steel	Chrome	26 - 55	26	1990	10		
A2135-2000W	Regular	Fixed	Stainless steel	Off white	26 - 55	26	1990	10		



Opening White



Opening Stainless steel

Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]		
Rectangular Portlight 700 x 191 mm Opening acrylic										
A2320-190CH	Regular	Opening	Stainless steel	Chrome	8 - 43	14	2250	10		
A2320-190B-S	Regular	Opening	Black	Black	8 - 43	14	2250	10		
A2320-1900W	Regular	Opening	Stainless steel	Off white	8 - 43	14	2250	10		
A2320-1900W-S	Regular	Opening	Black	Off white	8 - 43	14	2250	10		
A2320-1900W-W	Regular	Opening	White	Off white	8 - 43	14	2250	10		

www.rutgerson.se





Opening Stainless steel

Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]	
Rectangular Portlight 428 x 179 mm Opening acrylic									
A2320-180CH	Regular	Opening	Stainless steel	Chrome	8 - 43	14	1650	10	
A2320-1800W	Regular	Opening	Stainless steel	Off white	8 - 43	14	1650	10	




Opening Stainless steel



Fixed Stainless steel

				•						
Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]		
Rectangular Portlig	Rectangular Portlight 370 x 164 mm Opening acrylic									
A2320-170B-S	Regular	Opening	Black	Black	8 - 46	14	1530	15		
A2320-170RF	Regular	Opening	Stainless steel	Stainless steel	8 - 20	14	1530	15		
A2320-1700W	Regular	Opening	Stainless steel	Off white	8 - 46	14	1580	15		
A2320-1700W-S	Regular	Opening	Black	Off white	8 - 46	14	1580	15		
A2340-170RF	Regular	Opening	Stainless steel	Stainless steel	21 - 40	40	1790	15		
A2340-1700W	Regular	Opening	Stainless steel	Off white	21 - 66	40	1750	15		
Rectangular Portlig	ght 370 x 164 mm Fix	ed acrylic								
A2125-170RF	Regular	Fixed	Stainless steel	Stainless steel	8 - 20	14	1010	10		
A2125-1700W	Regular	Fixed	Stainless steel	Off white	8 - 43	14	1200	10		
A2145-170RF	Regular	Fixed	Stainless steel	Stainless steel	21 - 40	40	1380	10		
A2145-1700W	Regular	Fixed	Stainless steel	Off white	28 - 66	40	1450	10		

Rectangular Cutout



Outer dimensions	Cut-out dimensions [mm]								
X x Y [mm]	А	A B							
Rectangular Portlight D	Rectangular Portlight Dimension Guide								
370 x 164	347	142	61						
402 x 195	380	173	61						
428 x 179	406	157	61						
700 x 191	678	169	61						

Curved-rectangular Portlights



Opening Stainless Steel




Opening White


Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]		
Curved-Rectangular Portlight 405 x 140 mm Opening acrylic										
A5320-1400W	Regular	Opening	Stainless steel	Off white	8 - 46	14	1200	10		
A5320-1400W-S	Regular	Opening	Black	Off white	8 - 46	14	1200	10		
A5320-1400W-W	Regular	Opening	White	Off white	8 - 46	14	1200	10		



Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]		
Curved-Rectangular Portlight 440 x 180 mm Opening acrylic										
A5320-1800W	Regular	Opening	Stainless steel	Off white ABS	8 - 46	14	1950	15		

Curved-Rectangular Cutout





Outer dimensions	Cut-out dimensions [mm]								
X x Y [mm]	A B		C Radius	D Radius	E Radius				
Rectangular Portlight dimension guide									
405 x 140	387	122	926	33,5	126				
439 x 182	405	160		924	283				



Round Portlights




Opening Stainless Steel



Opening Black

Part no	Туре	Function	Outer frame	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [g]	Glass Thickness [mm]		
Round Portlight 250 mm Opening acrylic										
A4320-250B-S	Regular	Opening	Black	Black	8 - 33	20	2120	15		
A4320-2500W	Regular	Opening	Stainless steel	Off white	8 - 33	20	2120	15		
A4320-2500W-S	Regular	Opening	Black	Off white	8 - 33	20	2120	15		
A4330-2500W	Regular	Opening	Stainless steel	Off white	27 - 46	30	2320	15		



	Round	Cutout
--	-------	--------

Outer dimensions X [mm]	Cut-out dimensions A [mm]				
Round Portlight Dimension Guide					
250	230				



Photo: Curtesy of Hallberg-Rassy

AIR Flush Portlights

Rutgerson proudly introduces its first portlight sizes in a new range of flushed portlights. This product is meant to be installed on a fixed acrylic (PMMA), Polycarbonate (PC) or tempered glass by gluing it in place. It is possible to adapt the product to different thicknesses of the fixed glass and the minimum thickness is 8mm. Rutgerson's AIR flushed portlight is lighter and less bulky than other solutions on the market. The portlight glass is completely flushed to the fixed glass from the outside. The frame that is glued to the fixed glass is made of anodised aluminium, the window is made of a high grade acrylic glass. The hinges are friction hinges, which means that the lid stays open by itself. Hinges, opening knobs and the remaining components are made of composite and acidproof stainless steel.





Rutgerson's AIR flushed portlight is CE approved for all types of boats, all kinds of water (Design Category A) and for appliance location area IIb, III and IV.

Like all other products from Rutgerson, the portlight is designed and produced in Marstrand, Sweden.

		Panel thickness	Mounting	Outer dimensions [mm]		Cutout- dimensions [mm]		Weight		
Part no	Product descrription	[mm]	method	Х	Y	R	А	В	С	[g]
Rectangular Po	Rectangular Portlight 700 x 191 mm Opening acrylic									
AF23100-150	AIR Flush Portlight 214x150	8-10*	Glue	214	150	20	159,6	95,6	19,9	545
AF23100-190	AIR Flush Portlight 366x190	8-10*	Glue	366	190	20	308	132	19,2	1150

* The standard portlight is adapted to be glued into a panel/glass nominal thickness 8 to 10 mm. Customized portlights adapted to be mounted into thicker panel/glass are available on order.



Core benefits

- Light and sleek design
- Adjustable to different fixed glass thickness
- Completely flushed to the fixed glass from the outside
- CE certified Portlight Area IIb, III and IV, Category A
- Made in Sweden





Part no	Product description	Portlight size [mm]
Mosquito net		
AF2490	Mosquito net for Flushed Portlight	214 x 150



Inner Frames










Part no	Product description	Function	Inner frame	Fits portlights size [mm]	Size [mm]
Oval Inner Frames	3				
A1480-20RF	Inner frame Stainless steel for Opening Oval Portlight	Opening	Stainless steel	403 x 204	410 x 207
A1480-20CH	Inner frame Chrome for Opening Oval Portlight	Opening	Chrome	403 x 204	414 x 213
A1480-200W	Inner frame Off white for Opening Oval Portlight	Opening	Off white	403 x 204	414 x 213
A1485-20RF	Inner frame Stainless steel for Fixed Oval Portlight	Fixed	Stainless steel	403 x 204	410 x 207
A1485-200W	Inner frame Off white for Fixed Oval Portlight	Fixed	Off white	403 x 204	414 x 213
Rectangular Inner	Frames				
A2480-17B	Inner frame Black for Rectangular Opening Portlight	Opening	Black	370 x 164	367 x 163
A2480 -17RF	Inner frame Stainless steel for Rectangular Opening Portlight	Opening	Stainless steel	370 x 164	367 x 163
A2480-170W	Inner frame Off white for Rectangular Opening Portlight	Opening	Off white	370 x 164	379 x 175
A2485-17RF	Inner frame Stainless steel for Rectangular Fixed Portlight	Fixed	Stainless steel	370 x 164	367 x 163
A2485-170W	Inner frame Off white for Rectangular Fixed Portlight	Fixed	Off white	370 x 164	379 x 175
A2480-18CH	Inner frame Chrome for Rectangular Opening Portlight	Opening	Chrome	428 x 179	440 x 188
A2480-180W	Inner frame Off white for Rectangular Opening Portlight	Opening	Off white	428 x 179	440 x 188
A2480-19B	Inner frame Black for Rectangular Opening Portlight	Opening	Black	700 x 191	712 x 202
A2480-19CH	Inner frame Chromed for Rectangular Opening Portlight	Opening	Chrome	700 x 191	712 x 202
A2480-190W	Inner frame Off white for Rectangular Opening Portlight	Opening	Off white	700 x 191	712 x 202
A2480-20B	Inner frame Black for Rectangular Opening Portlight	Opening	Black	402 x 195	408 x 201
A2480-20CH	Inner frame Chromed for Rectangular Opening Portlight	Opening	Chrome	402 x 195	408 x 201
A2480-200W	Inner frame Off white for Rectangular Opening Portlight	Opening	Off white	402 x 195	408 x 201
A2485-20CH	Inner frame Chromed for Rectangular Fixed Portlight	Fixed	Chrome	402 x 195	408 x 201
A2485-200W	Inner frame Off white for Rectangular Fixed Portlight	Fixed	Off white	402 x 195	408 x 201
Elliptical Inner Fra	mes				
A3480-19RF	Inner frame Stainless steel for Elliptical Opening Portlight	Opening	Stainless steel	450 x 195	455 x 198
A3480-19CH	Inner frame Chromed for Elliptical Opening Portlight	Opening	Chrome	450 x 195	465 x 210
A3480-190W	Inner frame Off white for Elliptical Opening Portlight	Opening	Off white	450 x 195	465 x 210
A3480-22RF	Inner frame Stainless steel for Elliptical Opening Portlight	Opening	Stainless steel	485 x 225	496 x 323
A3480-22CH	Inner frame Chromed for Elliptical Opening Portlight	Opening	Chrome	485 x 225	510 x 245
A3480-220W	Inner frame Off white for Elliptical Opening Portlight	Opening	Off white	485 x 225	510 x 245
A3485-19RF	Inner frame Stainless steel for Elliptical Fixed Portlight	Fixed	Stainless steel	450 x 195	455 x 198
A3485-190W	Inner frame Off white for Elliptical Fixed Portlight	Fixed	Off white	450 x 195	455 x 198
A3485-22RF	Inner frame Stainless steel for Elliptical Fixed Portlight	Fixed	Stainless steel	485 x 225	496 x 232
Round Inner Fram		^	·	·	
A4480-25B	Inner frame Black for Round Opening Portlight	Opening	Black	250	261
A4480-250W	Inner frame Off-white for Round Opening Portlight	Opening	Off white	250	261
Curved-Rectangul	lar Inner Frames				
A5480-140W	Inner frame Off white for Curved-Rectangular Opening Portlight	Opening	Off white	405 x 140	413 x 148
A5480-180W	Inner frame Off white for Curved-Rectangular Opening Portlight	Opening	Off white	440 x 180	452 x 195

Aluminum Templates



Part no	Product description	Portlight Size [mm]	Size template [mm]					
Aluminum templates								
A1999-209	Template for Oval Portlight	403 x 204	420 x 250					
A2999-169	Template for Rectangular Portlight	370 x 164	480 x 273					
A2999-179	Template for Rectangular Portlight	428 x 179	506 x 257					
A2999-189	Template for Rectangular Portlight	700 x 191	725 x 215					
A2999-199	Template for Rectangular Portlight	402 x 195	460 x 252					
A3999-199	Template for Elliptical Portlight	450 x 195	495 x 240					
A3999-229	Template for Elliptical Portlight	485 x 225	533 x 271					

Acrylic Glass

Tinted acrylic glass with integrated silicone rubber seal. Opening knobs included.







A3300-220

Part no	Product description	Portlight size [mm]	Glass size [mm]	Glass thickness [mm]						
Spare Acrylic G	Spare Acrylic Glass									
A1300-200	Acrylic glass for Oval Portlight Tinted	403 x 204	350 x 152	15						
A2300-170	Acrylic glass for Rectangular Portlight Tinted	370 x 164	315 x110	15						
A2300-180	Acrylic glass for Rectangular Portlight Tinted	428 x 179	375 x 125	10						
A2300-190	Acrylic glass for Rectangular Portlight Tinted	700 x 191	645 x 135	10						
A2300-200	Acrylic glass for Rectangular Portlight Tinted	402 x 195	350 x 145	15						
A3300-190	Acrylic glass for Elliptical Portlight Tinted	450 x 195	400 x 145	15						
A3300-220	Acrylic glass for Elliptical Portlight Tinted	485 x 225	435 x 175	15						
A4300-250	Acrylic glass for Round Portlight Tinted	250	200	15						
A5300-140	Acrylic glass for Curved-Rectangular Portlight Tinted	405 x 140	354 x 89	10						
A5300-180	Acrylic glass for Curved-Rectangular Portlight Tinted	440 x 180	387 x 130	10						

www.rutgerson.se



Mosquito Net










A1490

A2490

A3492

A6-001

Part no	Product description	Portlight size [mm]	Size mosquito net [mm]
Mosquito ne	t		
A1490	Mosquito net for Oval Portlight	403 x 204	355 x 154
A2490	Mosquito net for Rectangular Portlight	402 x 195	351 x 155
A2497	Mosquito net for Rectangular Portlight	370 x 164	313 x 111
A2498	Mosquito net for Rectangular Portlight	428 x 179	372 x 126
A2499	Mosquito net for Rectangular Portlight	700 x 191	647 x 140
A3492	Mosquito net for Elliptical Portlight	485 x 225	433 x 173
A3498	Mosquito net for Elliptical Portlight	450 x 195	393 x 140
A4490	Mosquito net for Round Portlight	250	198
A5492	Mosquito net for Curved-Rectangular Portlight	405 x 140	350 x 85
A5498	Mosquito net for Curved-Rectangular Portlight	440 x 180	385 x 128
A34925	Fixed Mosquito net for Elliptical Portlight	485 x 225	440 x 170
A34985	Fixed Mosquito net for Elliptical Portlight	450 x 195	395 x 143
A6-001	Universal Mosquito net for portlights	Universal	230 x 490



Part no	Product description
Spare Parts	
A1-001	Opening knob kit
A2-001	Hinge kit





HATCHES

Using the best materials available, stainless steel, acrylic and composite, we offer a stunning range of hatches. There are three ranges with different design and application. The hatch frames have no welded seams to maximise the strength and integrity when confronted with the worst elements at sea. All hatches are CE approved for Area 2a.

For detailed information, please see the specific hatch line.





Rutgerson round Classic Hatch





Photo: Curtesy of Windy Boats





Classic Hatches

Round Ø500 mm Half-round Ø500 mm Square 556x556 mm Square 456x456 mm Rectangular 556x276 mm



Master Flush Hatches

Square size 10 Square size 44 Square size 60



Multihull Escape Hatch

Rectangular 560x482 mm

Classic Hatches

Our Classic Hatch has an elegant, timeless design due to its seamless construction and mirror-polished frame. The hatch lid combines the highest grade Swedish stainless steel and acrylic glass. The frame is made of an extremely strong, UV-resistant composite material. The classic range is designed to compliment the aesthetics of all types of boats.

The hatches are available in different shapes: Round, square, half-round and rectangular. The thickness of the acrylic glass for the Classic Hatch range is 10mm.



H0211-5203



H1111-5503




H0111-4403





H0311-0503

				Cut-out dimensions [mm]				
Part no	Product description	Outer Dimension X x Y [mm]	Height [mm]	A	в	C Radius	D Radius	Weight [g]
Classic Hatch		^						
H0311-0503	Classic Round Hatch with Off white inner frame	530 x 545	27	Ø482				4200
H1311-0503	Classic Round Hatch with Air vent and Off white inner frame	530 x 545	27	Ø482				4700
H0411-2503	Classic Half-round Hatch with Off white inner frame	570 x 380	27	522	312	51	265	3800
H0111-4403	Classic Square Hatch with Off white inner frame	456 x 456	27	408	408	34,5		4200
H0111-5503	Classic Square Hatch with Off white inner fr-ame	556 x 556	27	508	508	34,5		7000
H1111-4403	Classic Square Hatch with Air vent and Off white inner frame	456 x 456	27	408	408	34,5		4950
H1111-5503	Classic Square Hatch with Air vent and Off white inner frame	556 x 556	27	508	508	34,5		7100
H5111-4403	Classic Square Hatch with Stay and Off white inner frame	456 x 456	27	408	408	34,5		4400
H5111-5503	Classic Square Hatch with Stay and Off white inner frame	556 x 556	27	508	508	34,5		7500
H0211-5203	Classic Rectangular Hatch with Off white inner frame	276 x 556	27	508	228	34,5		4100

Classic Hatch Cutout









Master Flush Hatches version 2

Rutgerson's popular Master Flush hatch assortment has now evolved to a new design called v2 (version 2). The new design elements include a new handle design, flushed hinge concept, a new manual stay and the option to not have any outer handles. As with our original design, the hatch is flushed but requires a recess on the deck. Once the recess is in place, however, the hatch is easy to install. The hatches consist of a faced, 12mm tinted acrylic glass and a frame made out of a high-tech composite. The combination of clever construction and the unique innovation of a composite frame results in the lightest and most durable hatch on the market. The Master Flush range is available with a durable anti-slip tape, the article number ends with "AS". Conforms to the CE standards EN ISO 12216:2002, EN ISO 9094-1 and EN ISO 9094-2.








F	6000-2411	H440	0-2411					H10	00-2	401	
				Outer dimensions [mm]		Height [mm]		Cut-ou nsions	-	\A/=:=h+	
Part no	Product description	Inner / Outer handles	Stay	Х	Y	R	Н	А	В	С	Weight [g]
Master Flush Hatch											
H1000-2401	Master Flush Hatch 10	Composite	Friction hinges	330	330	10	31	260	260	42,5	2500
H1000-2401AS	Master Flush Hatch 10 with Anti Slip	Composte	Friction hinges	330	330	10	31	260	260	42,5	2500
H1000-2403	Master Flush Hatch 10	Composite/Stainless steel	Friction hinges	330	330	10	31	260	260	42,5	2600
H1000-2405	Master Flush Hatch 10	Stainless steel	Friction hinges	330	330	10	31	260	260	42,5	2900
H4400-2411	Master Flush Hatch 44	Composite	Manual	512	512	10	31	442	442	42	5600
H4400-2411AS	Master Flush Hatch 44 with Anti Slip	Composite	Manual	512	512	10	31	442	442	42	5600
H4400-2413	Master Flush Hatch 44	Composite/Stainless steel	Manual	512	512	10	31	442	442	42	5900
H4400-2415	Master Flush Hatch 44	Stainless steel	Manual	512	512	10	31	442	442	42	6400
H6000-2411	Master Flush Hatch 60	Composite	2 x Manual	577	577	10	31	506	506	40	6800
H6000-2411AS	Master Flush Hatch 60 with Anti Slip	Composite	2 x Manual	577	577	10	31	506	506	40	6800
H6000-2413	Master Flush Hatch 60	Composite/Stainless steel	2 x Manual	577	577	10	31	506	506	40	7100
H6000-2415	Master Flush Hatch 60	Stainless steel	2 x Manual	577	577	10	31	506	506	40	7600

Master Flush Hatch Cutout





H6000-2411AS

Multihull Escape Hatch

The Rutgerson Escape Hatch is made to be installed on the side of each hull on a catamaran or trimaran to provide a safe and reliable escape in case of capsizing. For safety reasons the hatch can be opened from both the inside and the outside. This is the only certified multihull escape hatch on the market with a flush design, which gives minimal resistance in the water and significantly reduces the pressure on the hatch. No recess or other adaption to the hull is needed.

The 12mm tinted acrylic glass is bolted to its frame and the hatch has double rubber seals for optimal waterproofness. The escape hatch comes with a light composite locking bar which prevents access from the outside when moored and falls off automatically if the boat capsizes. The hatch is CE-certified and approved according to the highest level (Area I) of ISO 12216 international standards for ocean sailing (Category A).



NOTE: This hatch should never be left open unattended. When under way, remove the locking bar and keep the hatch closed. Opening the hatch when sailing is strictly forbidden.




Core benefits

- Open from inside & outside
- Innovative flushed design
- Bolted glass
- Double rubber seals
- Stainless steel
- Made in Sweden

		Opening measurement	Outer dimensions	Cut o	Weight			
Part no	Product description	[mm]	X x Y [mm]	А	В	C Radius	[g]	
Multuhull Esca	pe Hatch							
H2255-5400	Multihull Escape Hatch, Rectangular	482 x 382	560 x 482	523	423	61,5	7500	
H2255-5403	Multihull Escape Hatch, Rectangular with OW inner frame	482 x 382	560 x 482	523	423	61,5	8000	







Hatch Accessories







H72-523



H73-053

H74-253

Part no	Product description	Color	Dimension [mm]	Weight [g]			
Classic Hatch Inner frames							
H71-443	Inner frame Off white for Classic Hatch 456x456	Off white	456 x 456	350			
H71-553	Inner frame Off-White for Classic Hatch 556x556	Off white	556 x 556	420			
H72-523	Inner frame Off-white for Classic Hatch 276x556	Off white	276 x 556	380			
H73-053	Inner frames Off white for Classic Hatch Ø500	Off white	Ø500	300			
H74-253	Inner frame Off-white for Classic Hatch Ø500 Half-round	Off white	Ø500 Half-round	300			




Part no	Product description	Color	Dimensions [mm]	Max depth [mm]	Weight [g]
Multuhull Esc	ape Hatch Inner frames				
H72-453	OW inner frame for Rectangular Multihull Escape Hatch	Off white	560 x 482	100	500



Part no	Product description	Size [mm]
Multihull Esca	pe Hatch Aluminum template	
H2999-549	Template for Rectangular Multihull Escape Hatch	560 x 482 x 4

	60)	7) <u>Cutout hole @100</u> Ø133	Air ver	nt	
Part no	Product description	Dimension [mm]	Height [mm]	Air opening [mm3]	Weight [g]
Air Vent					
H9-170	Air Vent, Stainless steel	173	40	655	3580



Part no	Product description
Universal Mosqu	uito Net
H9-001	Mosquito net for Hatches Universal



Photo: Curtesy of Catana.







H8-001

H8-004

H8-011





H5-001S





H8-001S

a 🖻





H8-004S

H8-012S

		Ro	Round		round	Squ	lare	Recta	ngular
Part no	Product description	Left	Right	Left	Right	Left	Right	Left	Right
Handles for Clas	Handles for Classic Hatch, looking from the hinge side								
H5-001	Composite handle	L		L			R		R
H5-002	Composite handle		R		R	L		L	

Part no	Product description	H1000-2401	H1000-2403	H1000-2405	H4400-2411	H4400-2413	H4400-2415	H6000-2411	H6000-2413	H6000-2415
Handles for Mas	ter Flush Hatch v2, looking for the hinge side. Standard assortment.									
H5-001	Composite handle for Classic and Master Hatch, left	1			1					
H5-001S	Composite handle for MFH v2, left*							1		
H5-002	Composite handle for Classic and Master Hatch, right									
H5-002S	Composite handle for MFH v2, right*				1			1		
H8-001	Stainless steel handle for MFH, left			1			1			
H8-001S	Stainless steel Handle for MFH v2, left*									1
H8-004	Stainless steel Handle for MFH, right									
H8-004S	Stainless steel handle for MFHv2, right*						1			1
H8-011	Stainless steel & Composit Handle for MFH, left		1			1				
H8-011S	Stainless steel & Composite Handle for MFH v2, left*								1	
H8-012	Stainless steel & Composit Handle for MFH, right									
H8-012S	Stainless steel & Composite Handle for MFH v2, right*					1			1	
Stay for Master F	lush v2									
H8-007	Manual Stay for Master Flush Hatch 44 v2				1	1	1			
H8-008	Manual Stay for Master Flush Hatch 60 v2							2	2	2

* With stay attachment




Photo: Curtesy of Catana.

DECKHARDWARE

BLOCKS

Rutgerson has a wide assortment of blocks to choose from suitable for both inshore and offshore sailing, ranging from dinghies to racing yachts and high latitude explorers. All our blocks are made in our factory in Marstrand, Sweden. Extensive in-house sailing experience and innovative design together with high-tech materials and advanced production methods ensures that you can rely on our blocks in all weather conditions.



How to calculate the load on your block

The block load is determined by the angle and pulling force from the line. If the force is coming from the direct opposite side of the attachment point of the block, then the load factor will be 200%. So if you have 100 kg of force in the lines and the angle between them is 0° then the block load will be 200 kg. And if the line force is 150 kg and the angle is 100° then the block load will be 194 kg (150kg * 1,29 = 193,4). Knowing this you just have to make sure you buy a block with a higher safe working load (see block specification).



RAW Blocks

Rutgerson's popular plain bearing block has been relaunched under a new name: The RAW Block, an extremely reliable block with the best price on the market considering its strength.

This block is produced from a high-tech composite of such strength that no stainless-steel reinforcement is needed. Consequently, overall weight of the block is reduced.

The block is completely maintenance free, as the spherical plain bearings will never deform under static high loads like ball bearings do.

Furthermore, the RAW Block is available in many different sizes and comes with a range of different fastening alternatives which makes it extremely versatile on the boat.





For stand-up solutions see page. 36.

RAW Blocks 35mm



B300301B



B300302B



B300303B



B300304B



B300321B



B300322B





B300382B

B300384B B300383B



B300324B



B300361B



B300362B

B300381B

Core benefits

- High-tech composite material
- Spherical plain bearings
- Large range
- Extensive range of fastening alternatives
- Adjustable clam cleats
- For Line diameters of 3-8mm
- Made in Sweden

	Part no	Product description	A Sheave Ø [mm]	B Length [mm]	C Shackle pin Ø [mm]	Safe working load [kg]	Breaking load [kg]	Line diameter [mm]	Weight [g]
	RAW Block 3	35mm							
	B300301B	RAW Block Single	35	55	4	450	850	3 - 8	50
	B300302B	RAW Block Single w becket	35	75	4	450	850	3 - 8	56
	B300303B	RAW Block w cam	35	55	4	450	850	3 - 7	100
	B300304B	RAW Block Single w cam & becket	35	75	4	450	850	3 - 7	110
	B300305B	RAW Block Single for strap head	35	55		450	850	3 - 8	35
	B300321B	RAW Block Fiddle	35 / 20	80	4	450	850	3 - 8	62
ſ	B300322B	RAW Block Fiddle w becket	35 / 20	100	4	450	850	3 - 8	70
ô	B300323B	RAW Block Fiddle w cam	35 / 20	80	4	450	850	3 - 7	113
100 kg	B300324B	RAW Block Fiddle w cam & becket	35 / 20	100	4	450	850	3 - 7	121
	B300371B	RAW Block Double	35	55	5	450	850	3 - 8	91
cam	B300372B	RAW Block Double w becket	35	75	5	450	850	3 - 8	98
đ	B300381B	RAW Block Triple	35	55	4	450	850	3 - 8	100
ן loa	B300382B	RAW Block Triple w becket	35	75	4	450	850	3 - 8	107
Maximum load of cams is	B300383B	RAW Block Triple w cam	35	55	4	450	850	3 - 7	153
Max	B300384B	RAW Block Triple w cam & becket	35	75	4	450	850	3 - 7	160

www.rutgerson.se



RAW Blocks 50mm



B300501B





B300502B



B300503B





B300505B



B300521B



B300522B



B300582B



B300583B

B300584B



B300524B



B300561B



B300562B

B300581B

Core benefits

- High-tech composite material
- Spherical plain bearings
- Large range
- Extensive range of fastening alternatives
- Adjustable clam cleats
- For Line diameters of 4-12mm
- Made in Sweden

Part no	Product description	A Sheave Ø [mm]	B Length [mm]	C Shackle pin Ø [mm]	Safe working load [kg]	Breaking load [kg]	Line diameter [mm]	Weight [g]
RAW BI	ock 50mm							
B30050	1B RAW Block Single	50	80	5	700	1250	4 - 12	116
B30050	2B RAW Block Single with becket	50	100	5	700	1250	4 - 12	127
B30050	3B RAW Block Single with cam	50	80	5	700	1250	6 - 10	220
B30050	4B RAW Block Single with cam & becket	50	100	5	700	1250	6 - 10	231
B30050	5B RAW Block Single for strap head	50	80		700	1250	4 - 12	80
B30052	1B RAW Block Fiddle	50 / 25	118	5	700	1250	4 - 12	132
B30052	2B RAW Block Fiddle with becket	50 / 25	139	5	700	1250	4 - 12	163
B30052	3B RAW Block Fiddle with cam	50 / 25	118	5	700	1250	6 - 10	232
B30052	4B RAW Block Fiddle with cam & becket	50 / 25	139	5	700	1250	6 - 10	270
≌ B30057	1B RAW Block Double	50	80	6	700	1250	4 - 12	226
B30057	2B RAW Block Double with becket	50	100	6	700	1250	4 - 12	236
B30058	1B RAW Block Triple	50	80	5	700	1250	4 - 12	205
B30058	2B RAW Block Triple with becket	50	100	5	700	1250	4 - 12	225
B30058 B30058 B30058 B30058 B30058 B30058	3B RAW Block Triple with cam	50	80	5	700	1250	6 - 10	300
B30058	4B RAW Block Triple with cam & becket	50	100	5	700	1250	6 - 10	310

RAW Blocks 60mm



B300601B



B300602B



B300603B



B300604B



B300605B



B300621B

B300681B



B300622B







B300682B



B300683B



B300684B



B300661B



B300662B

Core benefits

- High-tech composite material
- Spherical plain bearings
- Large range
- Extensive range of fastening alternatives
- Adjustable clam cleats
- For line diameters of 6-14mm
- Made in Sweden

Part no	Product description	A Sheave Ø [mm]	B Length [mm]	C Shackle pin Ø [mm]	Safe working load [kg]	Breaking load [kg]	Line diameter [mm]	Weight [g]
RAW Block	60mm			<u>.</u>				
B300601B	RAW Block Single	60	94	6	1150	2100	6 - 14	205
B300602B	RAW Block Single with becket	60	118	6	1150	2100	6 - 14	220
B300603B	RAW Block Single with cam	60	94	6	1150	2100	8 - 12	305
B300604B	RAW Block Single with cam & becket	60	118	6	1150	2100	8 - 12	320
B300605B	RAW Block Single for strap head	60	94		1150	2100	6 - 14	154
B300621B	RAW Block Fiddle	60 / 35	142	6	1150	2100	6 - 14	265
B300622B	RAW Block Fiddle with becket	60 / 35	164	6	1150	2100	6 - 14	279
B300623B	RAW Block Fiddle with cam	60 / 35	142	6	1150	2100	8 - 12	370
B300623B B300624B	RAW Block Fiddle with cam & becket	60 / 35	164	6	1150	2100	8 - 12	375
B300661B	RAW Block Double	60	94	8	1150	2100	6 - 14	325
B300661B B300662B	RAW Block Double with becket	60	118	8	1150	2100	6 - 14	360
	RAW Block Triple	60	94	6	1150	2100	6 - 14	390
B300682B	RAW Block Triple with becket	60	118	6	1150	2100	6 - 14	404
B300681B B300682B B300683B B300684B	RAW Block Triple with cam	60	94	6	1150	2100	8 - 12	490
B300684B	RAW Block Triple with cam & becket	60	118	6	1150	2100	8 - 12	500



www.rutgerson.se



RAW Blocks 80mm



B300801B





B300805B





B300822B







Part no	Product description	A Sheave Ø [mm]	B Length [mm]	C Shackle pin Ø [mm]	Safe working load [kg]	Breaking load [kg]	Line diameter [mm]	Weight [g]	
Block 80mm	Block 80mm								
B300801B	RAW Block Single	80	130	10	2000	3600	10 - 16	557	
B300801BSS	RAW Block 80mm Single w Semi Swiveling head	80	130	10	2000	3600	10 - 16	557	
B300802B	RAW Block Single with becket	80	165	10	2000	3600	10 - 16	588	
B300805B	RAW Block Single for strap head	80	130		2000	3600	10 - 16	333	
B300821B	RAW Blockd Fiddle	80 / 50	195	10	2000	3600	10 - 16	744	
B300822B	RAW Block Fiddle with becket	80 / 50	225	10	2000	3600	10 - 16	750	

Core benefits

- High-tech composite materialSpherical plain bearings
- Large range
- Extensive range of fastening alternativesFor line diameters of 10-16mm
- Made in Sweden

RAW Cheek Blocks





Flat plate






Curved plate

Part no	Product description	A Sheave Ø [mm]	D Length [mm]	E Width [mm]	Safe working load [kg]	Breaking load [kg]	Line diameter [mm]	Weight [g]
Cheek Blook	s Flat Plate							
B300344B	RAW Cheek Block 35mm Flat plate	35	50	48	450	850	3 -8	70
B300544B	RAW Cheek Block 50mm Flat plate	50	80	45	700	1250	4 -12	133
B300644B	RAW Cheek Block 60mm Flat plate	60	98	57	800	1600	6 - 14	240
Cheek Block	s Horizontal Plate							
B300345B	RAW Cheek Block 35mm Horizontal plate ¹	35	74	20 / 37	450	850	3 - 8	70
B300545B	RAW Cheek Block 50mm Horizontal plate ¹	50	94	40 / 16	700	1250	4 - 12	133
B300645B	RAW Cheek Block 60mm Horizontal plate ¹	60	110	50 / 21	800	1600	6 - 14	240
Cheek Block	s Curved Plate				·		·	
B300346B	RAW Cheek Block 35mm Curved plate ²	35	50	44	450	850	3 - 8	70
B300546B	RAW Cheek Block 50mm Curved plate ²	50	79	45	700	1250	4 - 12	133
B300646B	RAW Cheek Block 60mm Curved plate ²	60	97	55	800	1600	6 - 14	240

M5 mounting screws

¹ Recommed profile radius 190 - 400mm ² Recommed profile radius 30 - 50mm





RAW Toggle-head Blocks





Fixed toggle-head 12

Fixed toggle-head 14

Toggle-head 12







B С D Safe Breaking A Line Sheave Ø Length Pin Ø Fork width working load load diameter Weight Part no Product description [mm] [mm] [mm] [mm] [kg] [kg] [mm] [g] Fixed Toogle-head B300301BF RAW Fixed Toggle-head Block 35mm 55 6 12 450 850 3 - 8 54 35 B300501BF RAW Fixed Toggle-head Block 50mm 50 80 6 12 700 1250 4 - 12 111 B300501BF14 50 8 700 1250 RAW Fixed Toggle-head Block 50mm 80 14 4 - 12 120 B300601BF12 94 6 2100 RAW Fixed Toggle-head Block 60mm 60 12 1150 6 - 14 183 B300601BF14 RAW Fixed Toggle-head Block 60mm 60 94 8 14 1150 2100 6 - 14 190 B300801BF RAW Fixed Toggle-head Block 80mm 80 130 8 14 2000 3600 10 - 16 390 Toogle-head B300301BT RAW Toggle-head Block 35mm 35 55 6 19 450 850 3 - 8 61 B300501BT RAW Toggle-head Block 50mm 50 80 6 12 700 1250 4 - 12 124 B300501BT14 RAW Toggle-head Block 50mm 50 80 8 14 700 1250 4 - 12 130 B300601BT RAW Toggle-head Block 60mm 60 94 6 12 1150 2100 6 - 14 197 B300601BT14 RAW Toggle-head Block 60mm 94 8 14 2100 6 - 14 206 60 1150 B300801BT RAW Toggle-head Block 80mm 80 130 8 14 2000 3600 10 - 16 443

RAW Blocks with Snap Shackle Fastening

The RAW blocks from Rutgerson are available with snap shackles. Simply add the ending S to the standard block article number. For example B300501BS. Note that the safe working load and breaking load differ when the block is fitted with a snap shackle.

Part no	Product description	A Sheave Ø [mm]	Safe working load [kg]	Breaking load [kg]				
Snap Shackles fastening								
B3003XXBS	RAW Snap Shackle Block 35mm	35	300	550				
B3005XXBS	RAW Snap Shackle Block 50mm	50	500	900				
B3006XXBS	RAW Snap Shackle Block 60mm	60	750	1700				
B3008XXBS	RAW Snap Shackle Block 80mm	80	1500	2700				



ROC Blocks

Rutgerson's new ROC Block range has an innovative roller bearing system which eliminates the need for extra side bearings. This allows the block not only to be extremely strong and durable, but also more price-competitive than any other equivalent block on the market.

The sides and the sheaves of the ROC Block are made of high strength aluminum anodized in black and come with a forged shackle in stainless steel.

The ROC Block is also available in a unique ball joint stand up version and has a variety of accessories which makes it very flexible and useful onboard.

Part no	Product description	Sheave Ø [mm]	Length [mm]	Shackle pin Ø [mm]	Safe working load [kg]	Line diameter Ø [mm]	Weight [g]	
ROC Block	ROC Block							
B400801	ROC Block 80mm, Single	80	180	10	2500	14	620	
B401001	ROC Block 100mm, Single	100	198	10	3500	16	820	







ROC Block Becket

This is a an extremely strong through-sheave becket solution made to fit the Rutgerson ROC Block 80/100, allowing it to be used in a large variety of setups onboard. The product consists of two halves of smoothly rounded centrepieces that are fitted together in the hub of the block, where a rope loop can be attached.

Part no	Product description	Max line Ø [mm]	Weight [g]			
ROC Block Becet						
B400812	Becket for ROC Block 80mm	14	16			
B401012	Becket for ROC Block 100mm	16	27			





ROC Block Ball Joint Stand-up

This ROC Block Stand-up solution is completely unique on the market. It has a ball joint which under load adjusts itself to the right angle and stays there. It is equally strong in all directions, and allows a leaning angle down to 50 degrees. It also has the lowest height of all stand-up solutions, which helps to prevent winch overrun.

The ball joint stand-up comes in a kit with a ROC block, which is available in two sizes. There are also two different versions to choose from, one standard which is bolted on deck and one through-deck.

Depending on diameter and angle the line exits as low as 42 mm above deck on the standard one, and down to 22 mm on the through-deck version.

The stand-up should be fitted with four M8 bolts with countersunk head. For full strength, use A4-80 quality or higher.

Part no	Product description	Sheave Ø [mm]	Base plate Ø [mm]	Safe working load [kg]	Weight [g]		
ROC Block Ball Joint Stand-up							
B400848	ROC Block 80mm with Ball Joint Stand-up	80	80	2500	1100		
B401048	ROC Block 100mm with Ball Joint Stand-up	100	80	3500	1300		
B400849	ROC Block 80mm with Ball Joint Stand-up (through deck version)	80	80	2500	1100		
B401049	ROC Block 100mm with Ball Joint Stand-up (through deck version)	100	80	3500	1300		



Spring Stand-ups

This Spring Stand-up solution allows the block to be held upright and pivot under load. It supports the block, improves the lead angle and prevents it from hitting the deck. It is available in two different sizes and optimized for the Rutgerson ROC Block 80/100 but can be used on a variety of blocks in similar size.





B300643

B400843

B401043

Part no	Product description	Safe working load [kg]	Base plate Ø [mm]	Weight [g]		
Spring Stan	Spring Stand-up					
B300543	Spring Stand-up for 50mm block	1265	50	127		
B300643	Spring Stand-up for 60mm block	1265	50	127		
B400843	Spring Stand-up for 80mm block	3850	75	215 (835 with ROC 80)		
B401043	Spring Stand-up for 100mm block	3850	75	273 (1097 with ROC 100)		

Part no Product description				
Spring Stand-up				
B100542 Stand-up spring for 50mm block				
B100642 Stand-up spring for 60mm block				
B100842 Stand-up spring for 80mm block				
B101042	Stand-up spring for 100mm block			



Mainsheet Tackles







R300600R



	B320680B	B320620B		B320520B		
Part no	Product description		System purchase	Block size [mm]	Line Ø [mm]	
Mainsheet Tackles						
B320520B	Mainsheet tackle 4:1, 50mm RAW Block, 20m spliced	line	4:1	50	8	
B320620B	Mainsheet tackle 4:1, 60mm RAW Block, 25m spliced	line	4:1	60	10	
B320680B	Mainsheet tackle 6:1, 60mm RAW Block, 35m spliced	line	6:1	60	10	



Chafe Cover


Chafe covers are used on blocks in order to protect the sail from chafing. A suitable application for the chafe covers would be for example on the lazy jacks, so that when the sail is lowered it will not be damaged by the blocks. The Chafe cover are made of a soft rubber and are available in black.

Part no	Product description					
Chafe Covers						
B600551	Chafe Cover, Black					



Wire Blocks

The Rutgerson wire block assortment has a vast range of application areas. They are made of Swedish high-grade stainless steel and are completely maintenance free. The wire blocks are perfect as for example back stay adjusters.



Deck Blocks

Rutgerson has developed two models of deck blocks, one is installed on top of the roof and the other is installed in the cockpit in order to lead the line. This block range was developed for the boat brand Sense, but it is applicable for a wide range of boats and applications. The blocks are made of anodized aluminium and a 50mm aluminium sheave with a kevlar reinforced bearing. This allows the block to reach a breaking load over 3 tons. The line dimensions are 8-14 mm.

Part no	Product description	Height [mm]	Width [mm]	Length [mm]	Sheave Ø [mm]	Line Ø [mm]	Safe working load [kg]	Hole spacing [mm]	Weight [g]
Deck Blocks									
B309500BR	Top roof block, 50mm	72	30	70	50	8 - 14	1800	55	192
B309501BR	Bottom roof block, 50mm	69	30	84	50	8 - 14	1800	50 & 65	216



B309500BR

B309501BR

ROC Deck Blocks


The latest member of our popular ROC Block family is an assortment of extremely strong and durable deck blocks in aluminum. They have the same innovative roller-bearing system as our reliable ROC Blocks, allowing easy line handling and incredibly low friction also under very high loads.


Thanks to a unique design these deck blocks permits the line to pass both under and over the top of the sheave, depending on your needs. This makes them very versatile onboard and particularly useful for leading halyards from mast bases over deck houses and coamings into the cockpit.


The ROC Deck Blocks are available with one, three or six 80mm sheaves. The versions with three and six sheaves are designed to be fitted with only four bolts each to facilitate the installation and eliminate the number of holes through deck. The single version is fitted with two bolts.

These ROC Deck Blocks are made of black hardcoat-anodised aluminum and come with 2-4 high strength acid-proof stainless steel bolts.

				Dimensions	[mm]				Safe		
Part no	Product description	A1 / A2 Length	B Width	C ¹ / C ² Length	Sheave Ø	Max Line Ø	D x E Hole spacing	Screw	working load [kg]	Breaking load [kg]	Weight [g]
ROC Decl	k Blocks										
B409081	Single ROC Deck Block	143 / 51	32	105 / 148	80	14	60	2 x M12x80	2500	4500	827
B409083	Triple ROC Deck Block	143 / 51	96	105 / 148	80	14	60 x 64	2 x M12x80	2500	4500	2340
B409086	Sextuple ROC Deck Block	143 / 51	192	105 / 148	80	14	60 x 64	2 x M12x80	2500	4500	4360
ROC Deck	Blocks Mounting Plate										
B409001	Mounting plate for Single Deck Block B409081		32	105			60				33
B409003	Mounting plate for Triple Deck Block B409083		96	105			60 x 64				102
B409006	Mounting plate for Sextuple Deck Block B409083		192	105			60 x 64				205









Core benefits

- Superior working load (max 2500kg)
- Extremely low friction
- Available with 1, 3 & 6 sheaves
- Easy installation
 - Made in Sweden







Foot Blocks

Foot blocks are a vital part of the deck equipment as they must be able to take very high loads. In fact, the loads imposed on foot blocks are among the highest that a running rigging can generate. Due to the construction and solid materials of Rutgerson foot blocks, the load to size ratio is among the best on the market.

Spherical plain bearings that are typical for Rutgerson blocks outperform ball-bearings constantly and this is also true for our foot blocks. Due to the plain bearing construction, all our blocks are also maintenance free. Another important advantage is the fact that they are stackable and reversible in order to maximise efficiency.

The foot block assortment is divided into two ranges, anodised aluminium sides and high-tech composite sides.





B319040B B319060B





B300081B




B309081 B309101



B309082

			Dii	mensions [n	nm]		Safe				
Part no	Product description	A Length	B Sheave Ø	C Hole spacing	D Jammer radius	Line Ø	working load [kg]	Breaking load [kg]	Sides & sheaves	Bolts	Weight [g]
Foot Blocks	with jammer									<u>.</u>	
B319040B	Foot Block 40mm with jammer	82	40	49	77	4 - 12	600	1200	Composite	2 x M6	126
B319060B	Foot Block 60mm with jammer	107	60	60	77	8 - 14	750	1500	Composite	2 x M6	192
Foot Blocks											
B300041B	Foot Block 40mm single	82	40	49		4 - 12	600	1200	Composite	2 x M6	96
B300061B	Foot Block 60mm single	107	60	60		8 - 14	750	1500	Composite	2 ×M6	162
B300081B	RAW Foot Block 80mm single	130	80	74 x 19		10 - 18	1500	3000	Composite	2 x M6 1 x M8	267
B309081	Foot Block 80mm single	130	80	74 x 28		10 - 18	2980	4200	Aluminum	3 x M8	550
B309082	Foot Block 80mm double	130	80	74 x 28		10 - 18	2980*	4200	Aluminum	3 x M8	871
B309101	Foot Block 100mm single	169	100	102 x 34		12 - 20	3900	8000	Aluminum	3 x M10	807

40 and 60 mm footblocks are stackable - *The upper block when stacked or double has half the SWL / BL Maximum holding load of the jammer 300 kg $\,$



SNATCH BLOCK


We are proud to introduce our first openable block ever: Rutgerson Snatch Block (RSB). This snatch block is very flexible and can be used on almost any block application on a boat or sail such as barber, hauler, genoa line. It's easy to remove and install on a line already under load. The block is designed with a Rutgerson Low Friction Ring and a strong Dyneema loop which is perfect for low load high speed or high load low speed applications.

The RSB is our lightest block yet with an incredible strength/weight ratio as well as an extremely high working load compared to dimension. It is also designed so that there are no loose parts. The block can be opened without risking to lose the low friction ring. The low friction ring is anodised with a unique hard-coat and Teflon-impregnated anodization with very low friction properties. The Dyneema loop has a diamond knot, which we have developed ourselves, that generates almost twice the strength to the loop shackle compared to a standard diamond knot shackle with the same line dimension.



				Dimensions [mm]			
Part No	Product description	Low Friction Ring	A Sheave Ø	B Length	Max Line Ø	SWL [kg]	Weight [g]
Rutgerson	Snatch Block						
RSB15	Rutgerson Snatch block size 15	LFR15X10	35	46	6	1600	30
RSB21	Rutgerson Snatch block size 21	LFR21X14	49	65	10	3200	78
RSB25	Rutgerson Snatch block size 25	LFR25X17	60	78	14	5200	135

NB! This product is not available in all countries. Please contact your Rutgerson dealer.



Please find product video: https://www.rutgerson.se



LOW FRICTION RINGS

Low friction rings provide a good alternative to blocks in most applications where the line movements are minimal and the loads are high. For example back-stays, reefing points, jibs' sheet leads and lazy jacks. Their versatility seems to have no limits on the boat.

The rings are extremely resistant and strong. Both cost and weight is low compared to blocks. Plus, with no moving parts maintenance is zero.

The assortment consists of five sizes, all made of high strength aluminum with an extremely durable and low friction hard-coat and Teflon impregnated anodazation in black.



			Dimensio	ons [mm]		Approx SWL	Packed		
Part no	Product description	Size	Max Line Ø	Hole Ø	Outer Ø	[kg]	Weight [g]	per	
Low Friction Rin	Low Friction Rings								
LFR7x5	Low Friction Ring	7 x 5	5	7	17,5	400	1,8	10	
LFR10x7	Low Friction Ring	10 x 7	7	10	24,5	800	5	10	
LFR15x10	Low Friction Ring	15 x 10	10	15	35	1600	16	10	
LFR21x14	Low Friction Ring	21 x 14	14	21	49	3200	42	10	
LFR25x17	Low Friction Ring	25 x 17	17	25	59,5	5200	72	10	



STAINLESS STEEL FITTINGS

Padeyes

The Rutgerson padeyes have an incredibly elegant and stream-lined design – a jewel on your deck! They are made of high quality stainless steel. The padeyes are excellent for mounting blocks on deck or as attachment points for safety lines, staysails, reefing blocks, jibe preventors and many other application areas.


Flexibility is the main characteristic of Rutgerson padeyes as they can be mounted practically anywhere and can take very heavy loads. They adjust themselves to the angle of the load and fold down when they are without load in order to minmize the risk of hurting the crew and equipment.




Rutgerson padeyes correspond to the declaration of "Man overboard prevention" SS-EN ISO 15085:2003.

			Di	mensions [m	m]		Safe working Breaking load				
Part no	Product description	А	В	С	D	ØE	load [kg]	[kg]	Weight [g]		
Padeyes							- -				
E030010S	Padeye 14	43	40	23	14	5,5	850	1500	66		
E030020S	Padeye 17	45	39	27	16	6,5	1100	2200	75		
E030030S	Padeye 20	60	58	35	21	8,5	1750	3500	184		







Core benefits

- Wide range of application areas
- Very high working load
- Stream-lined for aesthetic and practical reasons

Snap Shackle

A snap shackle is a fast action fastener which can be implemented single handed. It uses a spring activated locking mechanism to close a hinged shackle, and can be unfastened under load. This shackle is like our other shackles and hooks made of a high-quality stainless steel, namely AISI316.

Pelican Hook

The pelican hook is suitable for several areas of usage, such as the safety lines. The fitting is made of high-quality stainless steel, namely AISI316. Both the snap shackles and the pelican hook conform to the following standard:

Small craft - Man -overboard prevention and recovery ISO 15085:2003

Part no	Product description	Safe working load [kg]	Breaking load [kg]	Weight [g]	Dimensions [mm]
Stainless Steel F	ittings				
E050070	Snap shackle 70mm	800	1400	70	70 x 45
E050120	Snap shackle 120mm	1250	4000	227	120 x 70
E050075	Pelican hook	600	1200	67	75 x 45



E050070



E050075

ROPE CLUTCHES

 $L_{J} \cup L_{f} \cup f_{f}$

Rope Clutch RC75

Rutgerson rope clutches can take much higher loads than equivalent sizes of other manufacturers on the market due to a unique combination of clever construction and high-quality materials. The housing is made of a black high-tech composite of high strength, whereas the other parts are made of either anodized aluminium or stainless steel. You will find that the handling of the lines much easier with Rutgerson rope clutches. This is because it is the only rope clutch on the market fitted with an integrated low-friction sheave, which ensures that the line runs smoothly – both when winching and when hauling by hand. Naturally, the clutch allows continued trimming of the line even when it is in a locked position.

Core benefits

- Superior working load
- Easy and cleaver installation


Best in action

- Elegant design
- Minimum friction
- Made in Sweden




				Dimensions	[mm]			
Part no	Product description	A Height	B Width	C Length	D x E Hole spacing	Line Ø	Max load [kg]	Weight [g]
Rope Clutch	RC75X							
S600701	Single Rope Clutch RC75X	70	39	139	79 (M6 bolts)	8 - 12	750	352
S600702	Double Rope Clutch RC75X	70	66	139	79 x 27,5 (M6 bolts)	8 - 12	750	618
S600703	Triple Rope Clutch RC75X	70	94	139	79 x 27,5 (M6 bolts)	8 - 12	750	894
S600705	Rope Clutch RC75X 5 units	70	147	139	79 x 27,5 (M6 bolts)	8 - 12	750	1400
Rope Clutch	RC75S				^			
S600711	Single Rope Clutch RC75S	70	39	139	79 (M6 bolts)	4 - 8	440	352
S600712	Double Rope Clutch RC75S	70	66	139	79 x 27,5 (M6 bolts)	4 - 8	440	618
S600713	Triple Rope Clutch RC75S	70	94	139	79 x 27,5 (M6 bolts)	4 - 8	440	894
S600715	Rope Clutch RC75S 5 units	70	147	139	79 x 27,5 (M6 bolts)	4 - 8	440	1400





Max holding load (kg) per rope diameter (mm)



Rope Clutches 43

Rope Clutch RC120

The RC120 has been developed especially for modern types rope such as Lycra and Dyneema. The handle is equipped with a revolutionary needle-bearing, which gives the RC120 a performance that was unthinkable before. The new handle has a built-in friction function that ensures that the handle stays in one position, open or closed. Releasing the desired load requires little effort, even during very heavy loads. It is also possible to quickly and without effort close the rope clutch.








S601201

S601202


S601203

			•	Dimension	s [mm]						
Part no	Product description	A Height	B Width	C Length	D x E Hole spacing	Line Ø	Max load [kg]	Weight [g]			
Rope Clutcl	Rope Clutch RC120X										
S601201	Single Rope Clutch RC120X	81	41	160	70 and 85 (M6 bolts)	10 - 16	1200	624			
S601202	Double Rope Clutch RC120X	81	73	160	70 x 32 and 85 x 32 (M6 bolts)	10 - 16	1200	1119			
S601203	Triple Rope Clutch RC120X	81	105	160	70 x 32 and 85 x 32 (M6 bolts)	10 - 16	1200	1621			
Rope Clutcl	h RC120S				x						
S601211	Single Rope Clutch RC120S	81	41	160	70 and 85 (M6 bolts)	8 - 12	850	624			
S601212	Double Rope Clutch RC120S	81	73	160	70 x 32 and 85 x 32 (M6 bolts)	8 - 12	850	1119			
S601213	Triple Rope Clutch RC120S	81	105	160	70 x 32 and 85 x 32 (M6 bolts)	8 - 12	850	1621			





Max holding load (kg) per rope diameter (mm)



How to choose Rope Clutches

Which rope clutch you need depends on the needed maximal load capacity, the line diameter and the quality of the rope. The test for the diagram has been made with standard polyester ropes.



Rope Clutch RC2000

Rutgerson's largest rope clutch has the most innovative design yet and is completely unique on the market. It has been developed to take extreme loads up to 2 tons with minimal effect on the line. Despite the high loads the handle is incredibly smooth to release, you can lift it with one finger!

The housing is made of black anodised aluminium and the handle is made of polished aluminium o for a sleek, modern look.



WARNING! The larger rope clutches are developed to release the load easily, so make sure when releasing high loads not to keep your hands close to the rope entrance. Always put the line back on the winch before releasing the load for a safe line handling.

			Dimensions [mm]					
Part no	Product description	Height	Height Width Length Hole spacing Line Ø					
Rope Clutch RC	2000							
S602001	Single Rope Clutch RC2000	101	43	200	140	8 - 14	2000	1200




Part no	Product description
Rope Clutch Access	sories
S600001	Rope clutch labels
S600010	Spring package for RC75X / RC750HPX / RC750
S600015	Replacement handle for RC75X / RC750HPX / RC750
S600020	Sheave for RC75X / RC750HPX / RC750
S600025	Cam for RC75X / RC750HPX / RC750
S600026	Cam for RC75S
S601027	Spring package for RC120X / RC1000HPX
T609006	Sealant washer

DECK ORGANISERS

Aluminium Organisers

The Rutgerson Transatlatic Organiser with aluminum plates is available with two, three, four, five or six composite sheaves. The extensive range results in high flexibility, since sailors can choose sizes according individual preference and deck layout. They can be stacked on top of each other to maximise efficiency of space and each sheave is through-deck bolted, which results in a high breaking loads. Special bolts are available separately.



56

56

31

31

800

800

1800

1800

8 - 14

8 - 14

405

490

B600025Deck organiser 5 sheaves285B600026Deck organiser 6 sheaves340

M8 mounting bolts in all the fixing holes

Special Bolt Set

40

40

Nut and bolt suitable for Rutgerson deck organisers and footblocks.



Part no	Product description
Special Bolt Set	
B290060-1	Special Bolt Set M6 x 80mm
B290060-2	Special Bolt Set M6 x 120mm
B290080-0	Special Bolt Set M8 x 60mm
B290080-1	Special Bolt Set M8 x 80mm
B290081-1	Special Bolt Set M8 x 100mm
B2900100-1	Special Bolt Set M10 x 80mm
B290100-2	Special Bolt Set M10 x 120mm



ROC Organisers

Rutgerson's ROC Organisers in aluminum are especially developed for smooth and safe line handling on big boats with high loads. Each sheave is bolted through deck and has a durable Kevlar bearing which together with the strong design gives a very low friction and superior breaking load. The ROC Organisers can be stacked on top of each other to maximize efficiency of the space on deck. This makes them exceptionally useful for leading multiple halyards or other lines aft to the safety of the cockpit.



Sides and sheaves are made of black hardcoat-anodized aluminum and shall be fitted with M12 countersunk head

screws (ISO 10642 or DIN 7991) with a maximum head diameter of 24mm. Screws are not included, and shall be chosen depending on deck thickness. To achieve maximum strength and our defined WL and BL we recommend using screws of A4-80 quality. For that screw we recommend a tightening torque of 76 Nm +/- 5%. The optional mounting plate in aluminum is made for the ROC Organiser assortment. Fitted under the deck, it spreads the force of the bolts over a larger area.

			Dimensio	ons [mm]		Safe			
Part no	Product description	A Length	B Sheave Ø	C Hole spacing	D Stack Height	working load [kg]	Breaking load [kg]	Line diameter [mm]	Weight [g]
ROC Organise	er								
B400022	ROC Organiser 2 sheaves	154	60	70	33	2500	4500	16	456
B400023	ROC Organiser 3 sheaves	224	60	70	33	2500	4500	16	678
B400024	ROC Organiser 4 sheaves	294	60	70	33	2500	4500	16	900
B400025	ROC Organiser 5 sheaves	364	60	70	33	2500	4500	16	1122
B400026	ROC Organiser 6 sheaves	434	60	70	33	2500	4500	16	1344
ROC Organise	er Mounting Plate								
B400022MP	Mounting plate for B400022	152		70	4				78
B400023MP	Mounting plate for B400023	222		70	4				117
B400024MP	Mounting plate for B400024	292		70	4				155
B400025MP	Mounting plate for B400025	362		70	4				194
B400026MP	Mounting plate for B400026	432		70	4				232



Core benefits

- Superior working load (max 2500 kg)
- Low friction
- Available with 2-6 sheaves
- Stackable
- Made in Sweden





DECK FILLERS

The range includes deck fillers for diesel, petrol, waste, water and deck access. As usual, Rutgerson's products bring something new and innovative to the market and in this case a unique link system. The link is made of the same material as cable ties, which is extremely strong compared to other composite materials. It is constructed so that it is incredibly easy to replace without any work from the inside, but just from the deck. The deck fillers are colour-coded in order to facilitate the distinction between different deck fillers. The design with high grade stainless steel and high tech composite is much more corrosion resistant compared to other solutions on the market such as casted steel.

The deck fillers for waste correspond to the standard ISO 8099.





Petrol



Waste





Water



Deck Access







Core benefits

- Light weight
- No corrosion
- No need for grounding
- Color-coded
- Reliable link-system
- Made in Sweden




				Dir	mensions [n	nm]			
Part no	Product description	A Outer Ø	B Height	C For hose	D Cutout	E Screw hole position	F Angle	Screw holes	Weight [g]
Deck Fillers Dies	sel					·			
CL038DIE-TL	Deck filler for Diesel, 38mm	Ø85	82	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	185
CL050DIE-TL	Deck filler for Diesel, 50mm	Ø85	85	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	186
CL054DIE-TL	Deck filler for Diesel, 54mm	Ø85	90	Ø54	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	193
Deck Fillers Petr	ol								
CL038PET-TL	Deck filler for Petrol, 38mm	Ø85	82	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	185
CL050PET- TL	Deck filler for Petrol, 50mm	Ø85	85	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	186
CL054PET- TL	Deck filler for Petrol, 54mm	Ø85	90	Ø54	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	193
Deck Fillers Was	ste*								
CL038WAS-TL	Deck filler for Waste, 38mm*	Ø85	130	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	215
CL050WAS-TL	Deck filler for Waste, 50mm*	Ø85	130	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	179
Deck Filler Wate	er					·			
CL038WAT-TL	Deck filler for Water, 38mm	Ø85	82	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	185
CL050WAT-TL	Deck filler for Water, 50mm	Ø85	82	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	186
Deck Filler Dec	k Access								
CL098ACC	Deck filler for Deck Access	Ø132	39		Ø101	Ø114,5	60° (6x)	Ø4,5 (6x)	360

*Complies with the global ISO 8099-standard for waste systems.

Deck Filler Accessories

Part no	Product description	
Deck Filler spar	e parts	
CLKEY	Deck Filler Key	
CLCDIE38-TL	Top Part for Diesel, 38mm Thread-lock	
CLCDIE50-TL	Top Part for Diesel, 50mm Thread-lock	
CLCDIE54-TL	Top Part for Diesel, 54mm Thread-lock	
CLCPET38-TL	Top Part for Petrol, 38mm Thread-lock	
CLCPET50-TL	Top Part for Petrol, 50mm Thread-lock	
CLCPET54-TL	Top Part for Petrol, 54mm Thread-lock	
CLCWAS	Top Part for Waste	
CLCWAT38-TL	Top Part for Water, 38mm Thread-lock	
CLCWAT50-TL	Top Part for Water, 50mm Thread-lock	
CLCACC	Top Part for Deck Access	
CLLINK	Link for Deck Filler with Bayonet-lock	
CLLINK38	Link for Deck Filler Fuel, 38mm with Thread-lock	1
CLLINK50	Link for Deck Filler Fuel, 50mm with Thread-lock	С
CLLINK54	Link for Deck Filler Fuel, 54mm with Thread-lock	



TRACK SYSTEMS

Mainsheet System

Control the power!

The mainsheet is one of the most exposed parts of a yacht's equipment due to the extreme level of stress during sailing. The Rutgerson mainsheet system increases the durability and performance of that part due to its clever construction and Roll-link function. The system is built up in modules, which makes it easy to adapt to different types of boat and specifications. The tracks and travellers are made of high-quality anodised aluminium.

Rutgerson is very proud to announce that the product was proclaimed "Best in Test" among other traveller systems available on the market according to a test performed by the German magazine Segeln in association with Chalmers University (Technical university in Sweden). The test was designed to give an objective measure of the sliding resistance under realistic conditions, with a vertical pre-load corresponding to rough weather conditions.

"It was found that the Rutgerson slider is superior in horizontal sliding under heavy conditions. Once again it was shown that Roll-links are clearly superior to ball bearings" (German magazine Segeln)


The unique construction of the track system renders the product completely safe. The travellers cannot be detached from the track by force or accident, so even if the product breaks under extreme conditions the traveller will stay attached to the track preventing injuries to the crew and the equipment.

Advantages with Roll-links:

- Maintenance free travellers that will always run smoothly due to the stainless steel link that keeps the rolls apart. This construction prevents any obstruction or clogging with salt or dirt. The roll-link "cleans itself" due to it's unique construction.
- Easy to assemble because the rolls are held together with a stainless steel link. The fact that all rolls are held together facilitates both installation and adjustment.
- The force is spread over a larger area, which results in a reduction in strain on the material. The balls in ball bearing systems will deform into an egg-shape under pressure and stop running smoothly. Roll-links will always retain their original shape.
- The higher stress on the product during rough weather conditions, the better performance.


How to choose Mainsheet System

Below you see which system we generally recommend, depending on the size of the boat.






Good to know when you choose contol line for your Mainsheet System



Control line load is approximately 0,2 x mainsheet load



How to choose track size and profile

The maximum load on the mainsheet track depends on the distance between the sides in the cockpit when the mainsheet track is unsupported. That distance is called the span length. To obtain the maximum load, measure the distance and insert into the graph.

This graph is a general guide to help sailors choose the correct track for their boat. This information is only true when the track has been fitted according to Rutgerson's instructions.

32mm Traveller

	T610112 T610122		Lore	T610001		TE10111	Leine	sour						
T610	112	T610122	101	0001		T610111	T6100	21						
	GENSON	NUTCEMEN	e of	e el e e		e el Ge el		C C C C C		C al C a		· · [a] [a] · ·	e e la faite	1
T610	0113	T610101	T61	0121		T610212	T610	222						
T620301 T620005				20006		end stops a avaiable in aluminium.	eet travellers, and tracks are black, anodized r the Part No.	1						
- Tunet		e of end stop	C	Dimensions [mm]										
Part no	Product des	scription		A ngth	B Width	Safe working load [kg]	Breaking load [kg]	Weight [g]						
32 mm Travel	lers													
T610112		car with shackle		78	67	500	3000	315						
T610122	Extra short o	car with stand-up		78	67	500	3000	325						
T610001	Short car wi			25	67	1000	4000	475						
T610111		th shackle and stopper		25	67	1000	4000	325						
T610021	Short car wi	1		25	67	1000	4000	485						
T610113		th stand-up and stopper		25	67	1000	4000	535						
T610101		r with shackle and sheave		55	67	1000	4000	585						
T610121	Standard car with stand-up and sheave			55	67	1000	4000	595						
T610212		th double shackle and sheave		35	67	2000	4000	1200						
T610222		th double stand-up and sheave		35	67	2000	4000	1300						
T620301		end stops with sheaves		38	67			500						
T620005		lunger stoppers		58	41			365						
T620006	Fixed plunge	er stoppers	E C	58	41			300						

All end stops are packed in pairs.

All mainsheet travellers, end stops and tracks are available in black, anodized aluminium. Add "B" to the part no.





Part no	Product description	Width [mm]	Height [mm]	Hole spacing [mm]	Fasteners	Weight [g/m]		
32 mm Tracks								
T600100	32mm track with stop hole	32	32	75	M6	1000		
T601100	32mm track for sliding bolt	32	32		M6	1000		
T601201	32mm track for sliding bolt, 2,0m bent 3,4m (Standard)	32	32		M6	2200gr/ pc		
32 mm High E	Beam Tracks			x				
T604100	32mm high beam track for sliding bolt*	32	50		M6	1900		
T606100	32mm high beam track with stop hole*	32	50	75	M6	1790		

Tracks are available in a maximum lenght of 6000mm and bolts required are M6 (32mm)

*Special washers are required for installation, part no T609016

Add "B" after partnumber for black anodized aluminium.


32mm Complete Mainsheet System



Part no	Product description	Length [m]	Width [m]	Safe working load [kg]	Breaking load [kg]	Recomended line Ø [mm]	Weight [g]		
Complete N	Complete Mainsheet system								
T690110	Complete mainsheet system, 32 mm track	1500	67	1000	4000	6 - 10	3100		

This 32mm mainsheets system comes as an assembled set, ready to be fitted on the deck. The control lines have to be acquired separately.

50mm Traveller



		Dimensio	ons [mm]			
Part no	Product description	A Length	B Width	Safe working load [kg]	Breaking load [kg]	Weight [g]
50 mm Traveller	S		^		<u>.</u>	
T610900	Short car with shackle	130	73	2000	5000	645
T610920	Short car with stand-up	130	73	2000	5000	690
T610901	Standard car with shackle and sheave	164	73	2000	5000	825
T610921	Standard car with stand-up and sheave	164	73	2000	5000	850
T610902	Long car with double shackle and sheave	235	73	3000	6800	1270
T610932	Long car with double stand-up and sheave	235	73	3000	6800	1360
T630501	Control line end stops with sheaves	88	73			510
T620905	Adjustable plunger stoppers	58	61			420
T620906	Fixed plunger stoppers	58	61			320

All end stops are packed in pairs. All mainsheet travellers, end stops and tracks are available in black, anodized aluminium. Add "B" to the part no.

B




50mm Tracks




Part no	Product description	Width [mm]	Height [mm]	Hole spacing [mm]	Fasteners	Weight [g/m]	
50 mm Tracks							
T603100	50mm track with stop hole	50	33	75	M8 with Ø 14mm head	1000	
T602100	50mm track for sliding bolt	50	33		M8 with Ø 14mm head	1500	
T602201	50mm track for sliding bolt, 2,0m bent 4,0m (Standard)	50	33		M8 with Ø 14mm head	3000gr/ pc	
50 mm High	Beam Tracks	^	^	<u>~</u>			
T605100	50mm high beam track for sliding bolt*	50	62		M8 with Ø 14mm head	3600	
T607100	50mm high beam track with stop hole*	50	62	75	M8 with Ø 14mm head	3240	

Tracks are available in a maximum lenght of 6000mm and bolts required are M8 (50mm) *Special washers are required for installation, part no T609018 Add "B" to part no. for black anodised aluminium



High beam 50mm



Accessories for Mainsheet Systems



Part no	Product description	Weight [g]	Part no	Product description	Weight [g]	
Accessories	s for 32mm & 50mm Mainsheet System	·				
T620351	Single sheave control line	120	T620352	Sheave control line and cleat	360	
T620353	Double sheave control line	230	T605011	End fitting for 32mm high beam track	890	
T620001	Composite end caps for 32mm track	60	T620901	Composite end caps for 50mm track	100	
T620002	Composite end caps for 32mm high beam track	6	T620902	Composite end caps for 50mm high beam track	20	
T600001	Spare stand-up for 32mm traveller	70	T600002	Spare stand-up for 50mm traveller	130	
T610132	Rubber stop for 32mm traveller	6	T610950	Rubber stop for 50mm traveller	6	
T609006	Sealent washers for 32mm track	1	T609008	Sealent washer for 50mm track	1	
T609016	Square washers for 32mm high beam track	7	T609018	Square washers for 50mm high beam track	14	
Roll-links						
T310502	Roll-links (20 rolls) that fit 32mm travellers T610111	, T610001, T	610101, T610	113, T610021, T610121, T610212, T610222	18	
T310504	Roll-links (24 rolls) that fit 32mm traveller T61019	2			22	
T310505	Roll-links (12 rolls) that fit 32mm traveller: T61011	2, T610122			14	
T310503	Roll-links (20 rolls) that fit 50mm travellers T610900, T610902, T610920, T610932					
T310506	Roll-links (24 rolls) that fit 50mm travellers T61090)1, T610921,	T610992		44	

www.rutgerson.se




Genoa Systems

It is possible to adapt our genoa system so that it perfectly matches your boat and your needs. The system is built up in modules with varying application. The genoa travellers come in three sizes for boats up to 60ft. There are two models available, one with a plunger stop for tracks with stop holes and the other with a 2:1 control line sheave for tracks with a concealed fastening mechanism.

The centre-pin pivoting main body permits alignment with the sheets, not only sideways but also across the traveller car. Another crucial advantage with the Rutgerson Genoa traveller is that the "head" stands up by itself, minimising the risk of chafing/tearing of the sheet. To use the traveller, either lock the car in place with the plunger stop or fix it in the open position for a "semi-floating" function.

Rutgerson genoa travellers can be smoothly adjusted under load due to a composite material fitted between the traveller and the track. The two sheaves

simulate one larger sheave, giving a low sheeting point and minimising chafing on all components. As with all our track systems, no maintenance is required.




How to calculate the load on your control line

The maximum load on the control line depends on the deflection of the sheet (Φ). In the graph you will find the load factor for the control line that corresponds to the different sheet angles. To obtain the control line load, multiply the sheet load with the control line load factor. If the sheet load is 100kg and the sheeting angle is 40 degrees, the control line load is 100 x 0,23 = 23kg.

How to choose Genoa System

Below you see which car for the genoa system we generally recommend, depending on the size of the boat.





Genoa System Travellers




www.rutgerson.se



32mm Genoa Tracks







Part no	Product description	Width [mm]	Height [mm]	Hole spacing [mm]	Fasteners	Weight [g/m]		
32 mm Genoa Tracks								
T652100	32mm track with stop hole	32	15	75	M6	850		

Special washers required for installation, part no. T609008.

Add "B" to part no. for black anodised aluminium



End Stops





T620007



Part no	Product description	Width [mm]	Height [mm]	Weight [g]		
End Stops						
T652001	End stops	39	38	38		
T620301	Control line end stops with sheave	88	67	248		
T620005	Adjustable plunger stoppers	58	67	185		
T620007	Friction stoppers	58	67	350		
All end stops comes in pairs.						

Accessories

Part no	Product description				
Accessories					
T609008	8mm Sealant washer				
T352915	Control line eye for traveller T652901, T652902 and T652903 for floating control				
T652900	Rubber part for Genua				



T609008





T652900

Track Systems 59

Self-tacking JIB System

The Rutgerson self-tacking jib system does all the work for you. It is built around our roll-link traveller system, which can be adjusted to fit all kinds of boats. The travellers can take oblique loads up to 45 degrees from vertical. Side friction is minimal due to the successful Roll-link concept. Our self-tacking jib system has been developed and tested to withstand the toughest conditions at sea.

The track can be bent horizontally, vertically or both in a compound bend. For tracks with a radius that is greater than 3700mm or smaller than 3400mm, a customised track can be ordered.

Like all our track systems, the self-tacking jib is completely maintenance free. Just rinse the track and traveller two or three times per season with fresh water.


In order to establish the correct bending radius for you boat, please do the following:

- 1. Measure the distance between the front of the mast and the headstay ("J" measurement).
- 2. The bending radius should be 95% of "J".
- 3. The radius can be altered from 3400mm to 3700mm by gently applying the full body weight onto the track with the upper surface facing down.



How to choose Self-tacking System

Below you see which system we generally recommend, depending on the size of the boat.







		Dimensions [mm]							
Part no	Product description	Length of track	Track Width	Radius	Rec boat size	Included articles	Article description		
32mm Self-tacking Jib System									
T690101	Self-tacking Jib System, up to 30ft*	2000	32	3400	Up to 30ft*	T390100 T601201 T610112 T620006	Self-tacking jib fittings 32mm track Extra short car with shackle Pair of fixed stoppers		
T690103	Self-tacking Jib System, up to 40ft*	2000	32	3400	Up to 40ft*	T390100 T601201 T610001 T620006	Self-tacking jib fittings 32mm track Short car with shackle Pair of fixed stoppers		
50mm Self-tacking Jib System									
T690191	Self-tacking Jib System, up to 50ft*	2000	50	4000	Up to 50ft*	T390190 T602201 T610900 T620906	Self-tacking jib fittings 50mm track Short car with shackle Pair of fixed stoppers		

* To be considered an approxmate measure.



For more information, please visit www.rutgerson.se



Made in Sweden since 1976

The Rutgerson company is a world leading manufacturer of yacht equipment, founded in 1976 by Swedish America's Cup sailor and entrepreneur Göran Rutgerson. Today the company is represented by distributors in more than 40 countries, but all our products are still made in Sweden as they always have been. For more information, please visit our website www.rutgerson.se.



Contact us Visit: Mjölkekilsgatan 21, 442 66 Marstrand, Sweden Call: +46 (0)303-20 66 50 Email: postmaster@rutgerson.se

Follow us Facebook: @rutgersonmarin Instagram: @rutgersonmarin



GENERAL WARRANTY & KEY TERMS OF SUPPLY BY RUTGERSON MARIN AB

A) Warranty

1) Period of Warranty

Rutgerson Marin AB issues a general warranty time durable for three years against malfunction or breakage from the date of delivery.

2) Warranty Coverage

Products sold by Rutgerson Marin AB and in normal and customary use, are conditionally warranted against malfunction or breakage. The warranty does not cover:

- i) Defects or damage resulting from use of the product in other than its normal and customary manner;
- ii) Defects or damage from misuse, accident or neglect;
- iii) Defects from improper testing, operation, maintenance, installation, alteration, modification or adjustment;
- iv) Damage from unauthorized repair or alterations;
- v) Damage from corrosive materials, ultra violet degradation, wear or tear beyond the specification of the case or enclosure.

3) Warranty Procedure of Service or Replacement

Notice of a claim for defect, service or replacement covered by this limited warranty shall be made promptly and in writing to the local Rutgerson distributor that supplied the product or to Rutgerson Marin AB. Products returned for service or replacement under this limited warranty must be assigned a valid RGA Return Goods Authorization number by Rutgerson Marin AB. Unidentified and unauthorized goods returned to Rutgerson Marin AB will NOT be approved or eligible for further investigation.

The customer is responsible for undertaking all expenses associated with transporting the goods to and from Rutgerson Marin AB or the local Rutgerson distributor that supplied the product. If the investigation of the product and the warranty claim reveals that the defect, malfunction or breakage is not covered by this limited warranty, the customer will be contacted and advised with respect to additional cost in conjunction with service or replacement.

For approved RGA goods, please send these together with assigned RGA documents to:

WARRANTY GOODS Rutgerson Marin AB Mjölkekilsgatan 21 SE-442 66 Marstrand SWEDEN

B) Purchase on Approval

Rutgerson Marin AB issues a general purchase on approval period durable for 60 days after delivery. Products that are subject for return needs to be unused and delivered to Rutgerson Marin AB in their original packing and according to the procedure stated in section (A3) above. Returned products will thereafter be subject to investigation and upon approval a 15% handling fee of the original purchase amount will be surcharged to all eventual credits. For all customized or one-off items, purchase on approval does not apply.

C) Supply

1) Packing Quantity

Products are supplied in stated packing and minimum purchase quantities only. For supply in smaller and/or customized quantities, additional terms will apply. For further information about alternative supply conditions, please contact Rutgerson Marin AB.

2) Delivery Time

All official delivery times endorsed by Rutgerson Marin AB are estimated and can be subject to changes. Rutgerson Marin AB is in the event of such related changes legislated to inform the customer.

3) Unanticipated Defects & Delays

Rutgerson Marin AB shall not be liable for unanticipated defects/delays, nor shall it be liable for any damage, whether direct or indirect, beyond the provisions set forth above or otherwise provided to customers under statutory law legislation. In connection with delivery of incorrect or defective goods, the customer must promptly submit a complaint to Rutgerson Marin AB.

D) Definitions

1) Safe Working Load (SWL)

Is the maximum static and/or dynamic load at which the product will still function without excessive friction, distortion, wear or permanent deformation of its components. Above this load, systems may fail, moving parts may seize and stainless steel or plastic components may begin to bend, stretch or otherwise deform. SWL should never exceed 55% of the breaking load (BL), and should never be exceeded in use.

2) Breaking Load (BL)

Is the load at, or around which, a major failure can be expected to occur to some part of the product's structure when new. Plastic components may split, rivets may give way, shackles may break and other metallic components may fracture. No product should be used at more than 55% of the breaking load.



The Rutgerson original philosophy

It is my firm belief that innovator, designer or manufacturer of yacht fittings should know the open sea in really bad weather to understand what is going on.

The Rutgerson staff have been out there...



Göran Rutgerson - 1976



Deck Hardware Distributor Network

Rutgerson Marin AB is represented on all continents by an impressive network of over 40 local distributors. All our distributors have a long tradition of serving our customers with dedication and knowledge of our products and their demands.

For updated information about our distributors, please visit www.rutgerson.se.

Rutgerson Marin AB Mjölkekilsgatan 21, SE-442 66 Marstrand, Sweden +46 (0)303-20 66 50, postmaster@rutgerson.se